

Xerox® AltaLink® Colour Multifunction Printers



C8130/C8135/C8145/C8155/C8170



AltaLink® C8100 Series Colour Multifunction Printers are built on Xerox® ConnectKey® Technology. For more information, go to www.ConnectKey.com.

System Specification	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Speed					
Colour/Black-and-White	Up to 30/30 ppm	Up to 35/35 ppm	Up to 45/45 ppm	Up to 55/55 ppm	Up to 70/70 ppm
Monthly Duty Cycle¹	Up to 90,000 pages	Up to 110,000 pages	Up to 200,000 pages	Up to 300,000 pages	Up to 300,000 pages
Hard Drive / Processor / Memory	Minimum 128 GB SSD / Optional: 500 GB HDD / Intel® Atom™ Quad Core 1.91 GHz / 4 GB system memory (8 GB system memory AltaLink C8170)				
Connectivity	Ethernet 10/100/1000 Base-T, High-speed USB 2.0 direct print, Wi-Fi/Wi-Fi Direct with optional Xerox® Dual Band Wireless Kit, NFC, Bluetooth (iBeacon)				
Controller Features	Unified Address Book, Remote Control Panel, Configuration Cloning, Fleet Orchestrator, Configuration Watchdog				
Optional Controller	Xerox® EX-c C8100 Print Server Powered by Fiery®				
Copy and Print					
Copy and Print Resolution	Copy: Up to 600 x 600 dpi; Print: Up to 1200 x 2400 dpi				
First-Print-Out Time (as fast as)	5.7 seconds colour/4.2 seconds black and white		4.9 seconds colour/3.8 seconds black and white	4.5 seconds colour/3.2 seconds black and white	3.8 seconds colour/3.0 seconds black and white
First-Copy-Out Time (as fast as) (from platen/ warmed up state)	6.1 seconds colour/4.5 seconds black and white		5.5 seconds colour/4.4 seconds black and white	4.7 seconds colour/3.7 seconds black and white	4.0 seconds colour/3.2 seconds black and white
Page Description Language	Adobe® PostScript® 3™, Adobe® PDF, PCL® 5c / PCL® 6				
Print Features	Print from USB, Print from Cloud Repositories (Dropbox, One Drive and Google Drive), Encrypted Secure Print, Xerox® Earth Smart Driver Settings, Job Identification, Booklet Layout, Store and Recall Driver Settings, Bi-directional Real-time Status, Scaling, Job Monitoring, Application Defaults, Two-sided Printing (as default), Hold All Jobs, Long-Sheet (Banner) Printing, Print Around, Print on Alternate Pages				
Mobile and Cloud Ready					
Mobile Connectivity	Near-Field Communication (NFC); Optional: Wi-Fi Direct, Wi-Fi (802.11 b/g/n/ac), AirPrint (iOS) including iBeacon (Bluetooth)				
Mobile Printing	AirPrint®, Mopria®, Xerox® Print Service (Android), @PrintByXerox App; Optional: Xerox® Workplace Mobile App (iOS/Android), AirPrint (iOS) including iBeacon (Bluetooth)				
Mobile Scanning	AirPrint®, Mopria®; Optional: Xerox® Workplace Mobile App (iOS/Android)				
Mobile Apps and Xerox® App Gallery	Automate everyday processes with apps that translate, redact, eSign, personalise print, convert, route, collaborate and communicate. Visit xerox.com/WorkplaceApps to find apps by industry or workflow. Software and services: Xerox® DocuShare® (xerox.com/ecm), XMPie® (xerox.com/XMPie), Xerox® Workplace Solutions (xerox.com/WorkplaceSolutions)				
Xerox® Workplace Suite and Xerox® Workplace Cloud	Optional: Xerox® Workplace Suite is a modular set of workflows designed to save customers time and money by providing effective control over their print fleet, while enabling worker productivity and mobility through a set of robust workflows. Xerox enables ultimate customer flexibility by offering these capabilities in both an on-premises server version (Workplace Suite) and with a cloud based-version (Workplace Cloud) of this solution.				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Scan	
Standard Features	Destinations: Scan to USB / Email / Network (FTP/SMB), HTTP, HTTPS, SFTP destinations; File Formats: PDF, PDF/A, XPS, JPEG, TIFF; Convenience Features: Scan Preview, Scan to Home, Searchable PDF, Single/Multi-Page PDF / XPS / TIFF, Password Protected PDF, Unified Address Book, Optical Character Recognition (OCR), Scan to Folder, 1-Touch Apps, TWAIN Support.
Optional Features	Scan to Cloud Repositories (Dropbox, One Drive and Google Drive) ² ; Xerox® Scanning App for DocuShare®, other solutions available through various Xerox Business Innovation Partners at xerox.com/Software-Solutions
Fax	
Standard Features	Internet Fax, Fax Build Job, Network Server Fax Enablement, Fax Build Job
Optional Features	Walk-up Fax (one-line and two-line options available, includes LAN Fax, Direct Fax, Fax Forward to Email or SMB Share)
Security	
Standard Features	802.1x, IPsec, HTTPS, SFTP and Encrypted Email, McAfee® Embedded Control Whitelisting, Firmware Verification, McAfee® ePolicy Orchestrator®, McAfee Enterprise Security Manager ² , LogRhythm SIEM ² , Splunk SIEM ² , Network Authentication, SNMPv3, SHA-256 Hash Message Authentication, TLS 1.1/1.2, Security Certificates utilizing ECDSA, Automatic Self-signed Certificate, Cisco® Identity Services Engine (ISE) integration, automated threat response through McAfee® DXL/Cisco® pxGrid integration, Local Authentication (Internal Database), FIPS 140-2 User Access and Internal Firewall, Port/IP/Domain Filtering, Audit Log, Access Control, User Permissions, Configuration Watchdog, TPM, Trusted Boot Encrypted Storage Drive (AES 256-bit, FIPS 140-2), Job Level Encryption via HTTPS and Drivers, Signed Email Under evaluation for Common Criteria Certification (ISO 15408), Encrypted Secure Print
Optional Features	McAfee® Integrity Control, Smart Card Enablement Kit (CAC/PIV/.NET) ³ , Xerox® Integrated RFID Card Reader, Encrypted Hard Disk (AES 256-bit, FIPS 140-2) with Image Overwrite, Xerox® Workplace Cloud/Suite Print Management and Content Security; learn more at xerox.com/WorkplaceSolutions
Print Management	
Standard Features	Xerox® Standard Accounting (Copy, Print, Scan, Fax, Email), Network Accounting Enablement
Optional Features	Xerox® Workplace Cloud/Suite, other network accounting solutions available through various Xerox Business Innovation Partners. Xerox® Virtual Print Management Service; learn more at xerox.com/PrintManagement

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Features and Accessories

Single-Pass Duplex Automatic Document Feeder (DADF)

saves time by simultaneously scanning both sides of two-sided documents, up to 270 impression per minute (ipm).



USER INTERFACE



Intuitive Tablet-Like 10.1-inch Colour Touchscreen is customisable and lets you perform tasks in just a few taps. Try it out at xerox.com/AltaLink8100UI.

PAPER INPUT⁴

Two 520-sheet Adjustable Trays (common with all configurations). Tray 1 handles media sizes up to A3 and Tray 2 handles media sizes up to SRA3.



Envelope Kit (optional – replaces Tray 1) provides feeding of up to 60 envelopes.



High-Capacity Tandem Tray

Configuration holds a total paper capacity of up to 3,140 sheets.

Four-Tray Module Configuration

(available for C8130/C8135) holds a total of up to 2,180 sheets.

Bypass Tray handles up to 100 sheets; Custom sizes: 89 x 98 mm to 320 x 1,320 mm.



High-Capacity Feeder

(optional) holds 3,000 sheets of A4 paper, increasing the maximum paper capacity to 6,140 sheets.



LONG SHEET PRINTING

Long Sheet Feed Kit (optional) provides the ability to print up to 320 x 1,320 mm media.



INNOVATIVE TECHNOLOGIES



Xerox® Integrated RFID Card Reader (optional) adds card-based authentication with support for over 90 access cards.



Near Field Communication (NFC) Tap-to-Pair allows users to tap their mobile device to the AltaLink C8100 Series user panel and quickly connect with the multifunction printer.



Smart Proximity Sensor detects when users are nearby. It conserves energy during inactive periods and automatically activates the device when a user approaches.

PAPER OUTPUT / FINISHERS⁴



Office Finisher (optional) provides advanced finishing functions, optional crease/score and saddle-stitch booklet, making it capable of 60-page booklets (2 to 15 sheets).



Business Ready (BR) Finisher (optional) gives you advanced finishing functions at a great value.



C-Fold/Z-Fold Unit (optional) adds C-fold, Z-fold and Z-half-fold to the BR Finisher or BR Booklet Maker Finisher.



BR Booklet Maker Finisher (optional) create 64-page saddle-stitched booklets (2 to 16 sheets).



Dual Offset Catch Tray (available when no finishers are installed; Single Offset Catch Tray with finishers).



Integrated Office Finisher (optional with C8130/C8135/C8145/C8155) provides 500-sheet stacking and 50-sheet, 2-position stapling.



Convenience Stapler (optional) staples up to 10 sheets of 75 gsm media.

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Device Specification					
Control Panel Languages	US English, International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Turkish, Greek, Russian, Czech, Polish, Hungarian, Romanian, Catalan, Arabic				
Accessories					
Optional	High-Capacity Feeder 3000 A4 Envelope Tray (Replaces Tray 1) Horizontal Transport Kit BR (Business Ready) Finisher (requires Horizontal Transport Kit) BR Booklet Maker Finisher (requires Horizontal Transport Kit) C-fold / Z-fold Unit for BR Finisher or BR Booklet Maker Finisher Convenience Stapler (includes Work Surface ⁵) Integrated Office Finisher (Available AltaLink C8130, C8135, C8145, C8155) Office Finisher Booklet Maker for Office Finisher Hole Punch (2/3, 2/4, Swedish) Office Finisher Smart Card Enablement Kit ³ Xerox® EX-c C8100 Print Server Powered by Fiery Walk Up Fax (One- or Two-line options, includes LAN Fax) Wi-Fi/Wi-Fi Direct with Dual Band Wireless Kit Bluetooth Kit McAfee® Integrity Control Enablement Kit USB Keyboard / Shelf Kit Xerox® Integrated RFID Card Reader Kit Unicode Font kit Foreign Device Interface (also known as Auxiliary Access Device) Interface for third-party access control devices, such as coin machines and card readers Long-Sheet Feed kit (banner printing) 500 GB HDD Scan To Cloud Enablement Kit				
Electrical Requirements	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
North America	Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 15 A				Voltage: 110-127 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 20 A
Europe	Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A				Voltage: 220-240 VAC +/- 10% Frequency: 50/60 Hz +/- 3%, 10 A

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Device Specification (continued)					
Power Consumption	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Running (Average)	115 V: 576 watts 230V: 586 watts	115 V: 600.3 watts 230V: 595.8 watts	115 V: 717 watts 230V: 674 watts	115 V: 806 watts 230V: 760 watts	115 V: 929 watts 230V: 908 watts
Standby Mode	115 V: 67 watts 230V: 71 watts	115 V: 64 watts 230V: 70 watts	115 V: 71 watts 230V: 71 watts	115 V: 72 watts 230V: 70.3 watts	115 V: 91.1 watts 230V: 79 watts
Auto Off/Sleep Mode	115 V: 0.69 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.69 watts 230V: 0.72 watts (Default time to sleep mode = 0 minutes)	115 V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.67 watts 230V: 0.71 watts (Default time to sleep mode = 0 minutes)	115 V: 0.68 watts 230V: 0.75 watts (Default time to sleep mode = 0 minutes)
Warm-up (from Off)	As fast as 85 seconds				
Recovery from Sleep	As fast as 4.5 seconds				
Operating Environment					
Required Temperature Range	10 to 28 °C				
Required Relative Humidity	15% to 85%				
Sound Power Levels	Operating: 63.7 / 64.2 dB(A) Standby: 4.0 / 4.0 dB(A)		Operating: 65.2 / 67.3 dB(A) Standby: 4.3 / 4.3 dB(A)		Operating: 70.4 dB(A) Standby: 4.3 dB(A)
Dimensions and Weight					
Base Configuration	Width: 620 mm Depth: 723 mm Height: 1,130 mm Weight: 143.1 kg				Width: 620 mm Depth: 793 mm Height: 1,169 mm Weight: 159.7 kg
With Integrated Office Finisher (C8130, C8135, C8145, C8155)	Width: 819 mm Depth: 723 mm Height: 1,130 mm Weight: 154.2 kg				N/A
With Office Finisher (with Booklet Maker)	Width: 1,207 mm Depth: 723 mm Height: 1,130 mm Weight: 182.5 kg				Width: 1207 mm Depth: 793 mm Height: 1,169 mm Weight: 199 kg
Base Configuration with Business Ready (BR) Finisher	Width: 1,395 mm Depth: 723 mm Height: 1,130 mm Weight: 187 kg				Width: 1,395 mm Depth: 723 mm Height: 1,169 mm Weight: 203.4 kg
Base Configuration with BR Booklet Maker Finisher	Width: 1,496.3 mm Depth: 723 mm Height: 1,130 mm Weight: 204 kg				Width: 1,496.3 mm Depth: 723 mm Height: 1,169 mm Weight: 220.6 kg
Base Configuration with BR Booklet Maker Finisher and C-fold / Z-fold Unit	Width: 1,632 mm Depth: 723 mm Height: 1,130 mm Weight: 254.3 kg				Width: 1,632 mm Depth: 723 mm Height: 1,169 mm Weight: 270.9 kg
Base Configuration with BR Booklet Maker Finisher, C-fold / Z-fold Unit and High Capacity Feeder	Width: 2,361 mm Depth: 723 mm Height: 1,130 mm Weight: 285.2 kg				Width: 2,361 mm Depth: 723 mm Height: 1,169 mm Weight: 302 kg
System Certification / Regulatory Compliance					
Certifications	To view the latest list of certifications, go to xerox.com/OfficeCertifications				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Paper Handling	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Single-pass Duplex Automatic Document Feeder (DADF)					
Capacity⁴	130 sheets				250 sheets
Speed (Up to)	82 ppm black-and-white and colour (simplex) 141 ipm black-and-white and colour (duplex)				135 ppm black-and-white and colour (simplex) 270 ipm black-and-white and colour (duplex)
Paper Sizes Sensed	85 x 125 mm to 297 x 432 mm				
Weights	60 to 128 gsm				
Bypass Tray (Standard)					
Capacity⁴	100 sheets				
Sizes	Custom Sizes: 89 x 98 mm to 320 x 1320 mm (SEF); Optional: Long Sheet Feed Kit (Banner Printing)				
Weights	52 to 300 gsm, Long sheets/banners (>19 in. / 483 mm) 28lb Bond - 120lb Index / 106 - 220 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies Long Sheets/Banners: Card Stock Card Stock Reloaded Lightweight Card Stock Lightweight Card Stock Reloaded				
Trays 1 and 2 (Standard)					
Capacity⁴	520 sheets each				
Sizes	Tray 1: Custom Sizes: 140 x 182 mm to 297 x 432 mm (SEF) Tray 2: Custom Sizes: 140 x 182 mm to SRA3 (SEF)				
Weights	52 to 300 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Paper Handling (continued)	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Four Tray Module (Trays 3 and 4) (Available on C8130/C8135)					
Capacity⁴	Tray 3: 520 sheets Tray 4: 520 sheets				
Sizes	Trays 3 and 4: 140 x 182 mm to SRA3 mm (SEF)				
Weights	52 to 300 gsm				
Media Types	Bond Card Stock Card Stock Reloaded Custom Envelopes Glossy Card Stock Glossy Card Stock Reloaded Heavyweight Card Stock Heavyweight Card Stock Reloaded Heavyweight Glossy Card Stock Heavyweight Glossy Card Stock Reloaded Hole punched Labels Letterhead Lightweight Lightweight Card Stock Lightweight Card Stock Reloaded Lightweight Glossy Card Stock Lightweight Glossy Card Stock Reloaded Plain Plain-Reloaded Preprinted Recycled Transparencies				
High Capacity Tandem Tray (Available with all models)					
Capacity⁴	Tray 3: 867 sheets Tray 4: 1,133 sheets				
Sizes	A4, JIS B5, Executive (7.25 x 10.5 in) LEF				
Weights	52 to 300 gsm				
Media Types	Bond Card Stock Custom Glossy Card Stock Hole Punched Labels Letterhead Lightweight Card Stock Lightweight Glossy Card Stock Plain Preprinted				
Envelope Tray (Optional – Replaces Tray 1)					
Capacity⁴	Up to 60 envelopes				
Sizes	No. 10 Commercial (9.25 x 4.125 in.) / Monarch, DL, C5 Custom Sizes: 98 x 148 mm to 162 x 241 mm				
Weights	75 to 90 gsm				
High-Capacity Feeder (HCF) (Optional with all models)					
Capacity⁴	3,000 sheets				
Sizes	Standard Sizes: A4 or B5 LEF				
Weights	52 to 300 gsm				
Total Capacity					
Device Total Capacity⁴	Four Tray Module: 2,180 sheets Four-Tray Module with High-Capacity Feeder: 5,180 sheets High-Capacity Tandem Tray Module: 3,140 sheets High-Capacity Tandem Tray Module with High-Capacity Feeder: 6,140 sheets				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Finishing	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Output Trays (Standard) (Dual Offset Catch Trays not available with Integrated Office Finisher and limited to one with Office Finisher and BR Finishers)					
Stacking Tray Capacity⁴	Dual Offset Catch Tray: Up to 250 sheets each Left Side Face-up Tray: Up to 100 sheets				
Integrated Office Finisher (Optional with AltaLink C8130/C8135/C8145/C8155)					
Stacking Tray Capacity⁴	500 sheets of 80 gsm – A4 or 250 sheets of 80 gsm – A3				
Sizes	89 x 98 mm to 297 x 432 mm				
Weights	52 to 300 gsm				
Stapling	Single / Dual Position Auto-Stapling: 50 sheets maximum: Letter / A4 / B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4 size sheets (less than 90 gsm or (2) 220 gsm covers)				
Office Finisher (Optional)					
Stacking Tray Capacity⁴	2,000 sheets unstapled or 1,000 sheets single stapled or 750 sheets dual stapled (A4)				
Stacking Tray Sizes	210 x 182 mm to 297 x 432 mm				
Weights	52 to 300 gsm				
Multiposition Stapling	50 sheets maximum: Letter / A4 / B5 size sheets (less than 90 gsm or (2) 220 gsm covers) 30 sheets maximum: Legal / Tabloid / A3 / B4 size sheets (less than 90 gsm or (2) 220 gsm covers)				
Hole Punch (Optional)	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole “Swedish” punch				
Booklet Maker for Office Finisher (Score/Crease, Saddle-stitch Staple) (Optional)					
Top Tray Capacity⁴	40 booklets (2-15 sheets per booklet – 80 gsm or less)				
Sizes	Letter – A4 SEF Legal – B4 SEF Tabloid – A3 SEF				
Saddle-Stitch Stapling	2-15 sheets / 8-60 page booklet 60 to 256 gsm				
Score / Crease	1-15 sheets / unstapled 60 to 105 gsm				
Business Ready (BR) Finisher (Optional) (Requires Horizontal Transport Kit)					
Capacity⁴	Offsetting Top Tray: 500 sheets Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position stapling) A3 or 200 sets (single-position staple) A4				
Sizes	100 x 148 mm x 320 x 488 mm for top tray 182 x 203 mm to 320 x 488 mm for stacking B5 to A3 for stapling				
Weights	52 to 300 gsm				
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported				
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole “Swedish” punch				
BR Booklet Maker Finisher (Optional) (Requires Horizontal Transport Kit)					
Capacity⁴	Offsetting Top Tray: 500 sheets of A4 unstapled Stacking Stapling Tray: 1,500 sheets of A4 / A3 unstapled or 200 stapled sets of A4 (single-position stapling or dual or 4-position stapling) or 100 stapled sets of A3				
Sizes	100 x 148 mm x 320 x 488 mm for top tray 182 x 203 mm to 320 x 488 mm for stacking B5 to A3 for stapling				
Weights	52 to 300 gsm				
Stapling	Single and multiposition stapling Auto stapling (50 sheets maximum) – 90 gsm Letter, Legal, Tabloid, A3, A4, B4 and B5 sizes supported				
Hole Punch	North America: 2/3-hole punch Europe: 2/4-hole punch Optional: 4-hole “Swedish” punch				
Booklet maker	Saddle-stitch 2 to 16 sheets (7 sheets at 106 to 176 gsm coated or 5 sheets at 177 to 220 gsm coated) Bi-fold up to 5 sheets Letter, Legal, Tabloid, A3, A4 supported				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Finishing (continued)	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
C-fold / Z-fold Unit (Optional with BR Finisher and BR Booklet Maker Finisher)					
Types	C-fold, Z-fold and Z-half-fold				
Capacity⁶	40 sheets				
Sizes	C-fold and Z-fold: Letter – A4 SEF only Z-half-fold: A3 only				
Weights	64 to 90 gsm				
Output Trays	Envelope Tray: C-fold, Z-fold and Tri-fold Stacker Tray or Top Tray: Z-half-fold				
Convenience Stapler (Optional - Includes Work Surface⁵)					
Capacity⁶	50-sheet stapling 5,000 staples Requires separate power outlet				
Copy	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
First-Copy-Out Time (from platen/warmed up Colour/Black-and-White)	As fast as 6.1 seconds / As fast as 4.5 seconds		As fast as 5.5 seconds / As fast as 4.4 seconds	As fast as 4.7 seconds / As fast as 3.7 seconds	As fast as 4.0 seconds / As fast as 3.2 seconds
Sides (input:output)	1-1, 1-2, 2-2, 2-1				
Quantity	1 to 9,999				
Resolution (max)	Up to 600 x 600 dpi				
Reduction / Enlargement	Variable zoom from 25% to 400% in 1% increments				
Concurrency	Program-ahead to allow a job to be queued while the initial job is processed (Copy, Print, Fax and Scan)				
Copy Features	Annotation and Bates™ stamping (with colour capability and font size adjustment) Authentication for Services (i.e. Colour Copy) Auto Paper Select Auto Reduction & Enlargement (to fit the selected paper size) Auto Tray Switching Automatic 2-sided / Duplex Booklet Creation Build Job (enables page-level programming and also lets you proof each section or delete the last section as the job is built) Collation Covers (front only, front and back, back only, printed inside and out: Blank or Printed) Dividers (blank) Edge Erase Features Help (Intuitive text and graphic descriptions) ID Card Copy Image Quality Adjustments Image Shift (with Auto Centre option) Invert Image (negative or mirror image) Large Job Interrupt Multi-up (up to 15 columns by 15 rows) Sample Set Save Job Settings Single Colour Stapling Transparencies				
Xerox® Copier Assistant®	Xerox® Copier Assistant® Software provides a PC-based alternative to the user interface touchscreen. Used in conjunction with a customer-supplied PC attached via the USB port, this software supports text-to-speech, screen magnification and easy PC keyboard access to basic and advanced copy features. Section 508 compliant. For more information or to download Xerox® Copier Assistant for free, visit xerox.com				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Print	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Resolution (up to)	1200 x 2400 dpi				
Print Features	Application Defaults Banner Sheet Enable/Disable Custom Colour Options (Colour by Words) Bi-directional Real-time Status Cover Selection Delay Print (specific time) User Permissions Image Options (Toner Saver, Resolution (Standard, Enhanced, High)) Job Identification (Print ID or Banner, Print ID in margins on first page only or all pages) LAN Fax (requires optional Fax Kit) Layout/Watermark N-up (up to 16 pages per sheet) Booklet Layout Long Sheet/Banner Finishing Fit to New Paper Size Hold All Jobs Paper Selection by Attribute Sample Set Saved Job (colour jobs can be printed as monochrome) Secure Print with Timed Deletion Special Pages (exception page programming: covers, inserts, exception pages) Store and Recall Driver Settings Sustainability Features (Xerox® Earth Smart Settings, Duplex, N-up, Turn-off Banner and Print ID, Smart Sample Set, Hold All Jobs) Two-sided Printing (as default) Print from Cloud Repositories (Dropbox, One Drive and Google Drive)				
Print from USB	Allows walk-up printing from Type A USB port on front panel Supports direct printing from computer via Type B USB port Supported file formats: PDF, JPEG, TIFF, PS, XPS, PCL Colour jobs can be printed as black-and-white				
Operating Systems	Windows Server 2008 SP2 (32- and 64-bit) Windows Server 2008 R2 (64-bit) Windows Server 2012 and R2 (64-bit) Windows Server 2016 (64-bit) Windows Server 2019 (64-bit) Windows 7 (32- and 64-bit) Windows 8 (32- and 64-bit) Windows 8.1 (32- and 64-bit) Windows 10 (32- and 64-bit) Mac OS 10.13, 10.14, 10.15 Fedora® Core Ubuntu®				
Network Protocols	TCP/IP: HTTP/HTTPS, Internet Printing Protocol, LPR/LPD, Raw Socket Printing/Port 9100, IPv4/IPv6, WSD Microsoft Windows Networking over IP Bonjour® / AirPrint® IPv6 Most protocols not in use can be disabled				
Font Capability	PCL: 93 scalable fonts, line printer and bitmap font (including Cyrillic font support) PostScript 3: 173 Type 1 fonts, 2 Multiple Master fonts				
Xerox® Global Print Driver®	A truly universal print driver that lets IT administrators install, upgrade and manage Xerox® and non-Xerox devices from a single driver. It provides a consistent, easy-to-use interface for end users, reducing the number of support calls and simplifying print services management.				
Xerox® Pull Print Driver	Makes it easy for IT managers to qualify, deploy and manage all print devices using a single driver in a Pull Print environment. Uses a single queue and single driver. The Xerox® Pull Print Driver extends convenience across a broad range of printing assets. IT administrators no longer need to manage and configure multiple drivers. Used in conjunction with Equitrac Office®, Ysoft® SafeQ®, Pharos® and others.				
Unified Address Book for Fax, Internet Fax, Email and Scan to...					
Features	Services supported: Fax, Internet Fax, Email, Scan to Maximum contacts: 5,000 Contacts: Supports 1 or more destinations Favourites for quick access of all services supported				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Scan	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Concurrency	Scan while the system is printing, copying or while it is transferring scan-to-network or fax jobs (priority is for the return of scanned originals and printing concurrent jobs)				
Input Speed (up to)	82 ppm black-and-white and colour (simplex) 141 ipm black-and-white and colour (duplex)			135 ppm black-and-white and colour (simplex) 270 ipm black-and-white and colour (duplex)	
Resolution	72 x 72 dpi to 600 x 600 dpi				
Bit Depth	1-bit (black-and-white), 8-bit (greyscale), 24-bit (colour)				
Maximum Scan Area	A3				
Scan Template Management	Support 250 scan templates Create Xerox® CentreWare® IS scan templates and share via device cloning to other multifunction printers' confirmation sheet options				
Network Protocols	SFTP, FTP, SMB, HTTP, HTTPS				
File Compression	Colour TIFF (TIFF 6.0 or TTN2 with JPEG, LZW) Black-and-white TIFF (G3MH, G4 MMR compression – single or multiple pages) Searchable PDF/OCR and PDF/A-1b (MRC, JPEG, G3 MH, G4 MMR, JBIG 2 Huffman, JBIG Arithmetic Compression, Deflate (for black-and-white and within MRC)) Linearised PDF / PDF/A				
Document Management Fields (Metadata)	Features only available in Network Scan-to-File Templates: <ul style="list-style-type: none"> • 1 to 6 user-programmable metadata fields per network scan to file templates and unlimited fields within the template – Metadata field consists of field name, default value and other configurations • Customised fields viewed on user interface for variable data input 				
Scan Features	Mixed Size Originals Scan Build Job Scan Preview Compression Quality/File Size Control Original Type (Photo and Text, Photo, Text, Map, Newspaper / Magazine) Auto Background and Shadow Suppression Size for Size (for mixed size originals) TWAIN Support / WIA 2.0 Support Bound Originals Edge Erase Reduction/Enlargement Single Touch Scan buttons (up to 10)				
Scan to Email (Standard)					
Scan Features	<ul style="list-style-type: none"> • Email signatures (6 lines each of 128 character max), email message body (user configurable), email Embedded Web Server confirmation sheet options • Scan to Email S/MIME Encryption • Email signing (requires Smart Card option) • Auto send to self 				
Directory Access	Address list via LDAP (Windows Active Directory, Exchange, Notes, Domino), Device Address Book				
Scan To					
Standard Features	Scan to USB Scan to Network Folder (using Secure FTP/HTTP/HTTPS) Scan to Home Scan to Network (using Secure FTP/HTTP/HTTPS) Scan to Email Scan to PC/Server Client (SMB or FTP) Scan to Mailbox				
Optional Features	Native Scan to Cloud Repositories (Dropbox, One Drive and Google Drive) ²				
Workflow Scanning (Optional)					
Scanning Software	Autostore v7 ecopy ShareScan v5.2 eCopy ScanStation v5.2				
Scanning Apps and Xerox App Gallery	Scan to/from: Dropbox™, Google Drive™, Microsoft® OneDrive®, Microsoft Office 365™, Box®, Xerox® Workplace Mobile App (iOS/Android) See the full list of apps available in the Xerox App Gallery: xerox.com/AppGallery				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Security	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Features	<ul style="list-style-type: none"> • Expanded Authentication <ul style="list-style-type: none"> - Network authentication to access device and/or device services via Kerberos (UNIX / Windows Server 2008), SMB (Windows Server 2008, Windows server 2012), NDS, LDAP authentication - Local Authentication (internal database) - Smart Card authentication – 144k CAC / PIV Card Support (2,048-bit certificate key) / .NET - Secure Data - Digitally signed PDF (when using Smart Card authentication) - Encrypted and authentication to SMTP server for Scan to Email - Encrypted / Password-Protected PDF (when using Email and Network Scan Templates only) - Secure Print (up to 10-digit PIN or Network Authentication) - Immediate Image Overwrite / Securely delete jobs using approved algorithms - On-Demand Image Overwrite (Scheduled, Manual), includes sanitation of unused area of disk - FIPS 140-2 256 bit Hard Disk Encryption, TLS, IPPS, HTTPS, SFTP, SNMPv3 • Expanded Authorisation <ul style="list-style-type: none"> - SA access based on network credentials - Authorisation per user per service - User Permissions required to access Print and Print Features (e.g. colour access or time restrictions) reflects in the print driver - Secure Network Access • Configuration Watchdog (Monitor and remediate 29 security settings): <ul style="list-style-type: none"> - Front USB Port 2 - Rear USB Port 1 - Rear USB Port 2 - Password Reset Access Control - 802.1x - Email Alerts - Group 1, 2 and 3 addresses, enablement, Recipient Group Preferences - Hold all jobs - Reprint Saved Jobs - Scan to Mailbox enablement - Fax Passcode length - System timeout - Show/Hide Login Name - PostScript® Passwords - Remote Services Set-up Supplies / Consumables: Enablement - Remote Services Set-up Supplies / Consumables: Software Download - Remote Services Set-up Supplies / Consumables: Feature Activation - Remote Services Set-up Supplies / Consumables: Update Device Settings - Remote Services Set-up Supplies / Consumables: Daily Synchronisation Time - Remote Services Set-up Supplies / Consumables: Automatically Send Diagnostic Information - FIPS 140-2 Encryption - Firmware Updates (Firmware Upgrade) Enable/Disable - Scheduled Upgrade - SNMP V1/V2 Protocols: Enable/ Disable Services - Scan services on multifunction printers - Remote Start (TWAIN) Scan services on multifunction printers - Scan Workflow Management - PII - Conceal Job Names - PII - Show Concealed Job Names in Network Accounting Reports - PII - Show Concealed Job Names in Audit Logs • IP Filter, IPsec, IPv6, TLS v1.0, v1.2, SNMPv3, HTTPS, 802.1X, SFTP • McAfee® Embedded Control (whitelisting), McAfee® Integrity Control (optional) • Port disablement including USB ports • Audit Log • Hide Print Job Names • Cisco® Identity Services Engine (ISE) compatible • Security Information and Event Management (SIEM) support for McAfee Enterprise Security Manager, LogRhythm and Splunk² • Full System Common Criteria certified by NIAP under HD Protection Profile for Hardcopy Devices v1.0 (HCD-PP v1.0)⁷ 				
Xerox® Integrated RFID Card Reader (Optional kit)	Integrated support for most industry security cards providing additional security; with embedded multifunction printer card readers in the multifunction printer panel.				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Fax	AltaLink® C8130	AltaLink® C8135	AltaLink® C8145	AltaLink® C8155	AltaLink® C8170
Network Server Fax Features					
Compatibility	ITU (CCITT) group 3; Various Xerox Business Innovation Partner Solutions				
Maximum Scan Area	A3				
Fax Send Features	One- or Two-sided Scanning (up to A3) Add to Send List (200 numbers maximum) Build Job, Favourites, Delay Send (specific time) Original Type (photo, text or photo and text)				
Fax Print Features	One- or Two-sided Printing, Staple, Secure Print				
Transmission Resolution	Superfine: 400 x 200 dpi (Scan at 600 x 600 dpi) Fine: 200 x 200 dpi Standard: 200 x 100 dpi				
Internet Fax Features					
Compatibility	Direct print-ready document transmission to remote Internet Fax machines or email clients (SMTP) Reception and automatic printout of documents sent via email from remote Internet Fax machines or email clients				
Directory Access	Utilises the Unified Address Book				
Send / Receive	Send: Multi-page TIFF, PDF, PDF/A Receive: TIFF, MTIFF, PDF, PDF/A, PS, text, PCL, PRN, JPEG				
Resolution	72 x 72 dpi to 600 x 600 dpi Bit Depth: 1-bit (black-and-white)				
Network Protocols	SMTP (send), POP3 (receive)				
Compliance	ITU-T T.37				
Walk-up Fax Features (Optional; Customer-Installable – 1 and 2 lines)					
Compatibility	ITU (CCITT) Group 3				
Speed / Modems	One or Two V.34 modems: 33,600 bps. Less than 4 seconds per page transmission time				
Compression / Speed	MH/G3, MR/G3, MMR/SG3, JBIG/SG3				
Resolution	Walk-up Send: Standard: 200 x 100 dpi Fine: 200 x 200 dpi Superfine: 600 x 600 dpi Receive: Accepts all sizes				
Fax Send Features	LAN Fax (fax from print driver) Auto Fax Transmission Reduction Page-by-page Job Status at the Machine Delay Start, Build Job, Favourites Automatic Memory Resend Automatic Cover Sheets PSTN Fax Batch Send (up to memory capacity) Device Address Book (up to 5,000 contacts)				
Fax Receive Features	One- or Two-sided Printing Stapled or Unstapled Receive Print Mode – Manual (size, margin, stock, header) / Auto Output Tray Selection Up to 200 Password-Protected Mailboxes Secure Receive Receive Timestamp Auto Answer Delay				
Fax forward	Forward to Email or SMB Location Fax Forward on Receive Only				
Fax Reports	Activity, Dial Directory, Group Directory, Transmission Confirmation, Pending Fax, Options Report, On Demand Overwrite Report, Mailbox Report, Broadcast Report				
Directory Access	Utilises the Unified Address Book Group fax available				
Auto Redial	Up to 14 attempts (per country requirements) 1 to 25 minute intervals				
Auto Resend	Up to 5 attempts				

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Device Management	
Administrative Protocols	DHCP, BOOTP, SNMP, SLP® v2, HTTP, HTTPS, DHCP Autonet, TLS, NTP, DNS, SMB, SMTP/POP3, WSD, LDAP, Multicast DNS
Management Support	SNMP Version 1, SNMP Version 2c and SNMP Version 3 trap over TCP/IP and IP MIB access (IETF-MIBII RFC 1213) Host Resources MIB RFC 2790, Printer MIB RFC 3805, PWG-Imaging-System- Power MIB, Configuration Orchestrator, Configuration Watchdog
Xerox® CentreWare® Web	A web-based server application for network administrators that permits web browser-based device management from any workstation, whether running Windows, UNIX or any other operating system: <ul style="list-style-type: none"> • Works with any SNMP-managed printer from any manufacturer. • Provides help with device discovery and installation, health checks and troubleshooting, and device upgrades, as well as basic accounting and asset management. • Requires Windows 7 and Internet Explorer 6.0 and higher. • Auto-detect Xerox® CentreWare® Web server and download configurations files for touchless remote installation
Xerox® Device Manager	Xerox® Device Manager collects and manages the data that drives fact-based decisions for your enterprise device management environment. It is a single tool to install print queues and configure, manage, monitor and report on both networked and locally connected devices – regardless of vendor – across your enterprise. Xerox® Device Manager provides: <ul style="list-style-type: none"> • Device monitoring and troubleshooting • Extensive reporting and discovery of new devices • Usage collection, chargeback and billing capabilities • Auto-detect Xerox® Device Manager server and download configurations files for touchless remote install
Fleet Orchestrator	The Fleet Orchestrator feature offers the ability to create a group of devices that share information with each other via a secure peer-to-peer connection. The following data can be shared: Software update files, clone files and 1-Touch App files.
Novell NDPS/NEPS	Server gateway application: centralised management tool.
Xerox® Device Types for SAP Environment	Xerox, together with SAP through our Gold-level membership in the SAP Printer Vendor Programme, provides seamless connectivity between SAP systems and your Xerox® printers and multifunction printers. As an SAP customer, you benefit from having SAP-certified Xerox® device types available right from SAP's online delivery model. SAP-certified device types for Xerox® printers and multifunction printers are available to download. office.xerox.com/Software-Solutions
Xerox® Device Types for SAP R/3 Intelligent Barcode Utility (optional)	Provides built-in process intelligence that allows the printing of barcodes on any appropriately configured PostScript printer in specific versions of SAP environment and within Latin-1 (ISO8859-1) SAP system code pages only. Used in conjunction with Xerox® PostScript Device Types for SAP environment and Xerox® Font Centre Barcode Fonts. Information available at office.xerox.com/Software-Solutions
Xerox® Barcode Pro PS (optional)	Enables intelligent PostScript printing on Xerox® multifunction printers by storing Xerox® software, as well as the barcode fonts on the printer hard disk. Enables the printing of barcodes from any application (SAP client or mainframe) that supports PostScript printing. Information available at office.xerox.com/Software-Solutions
Xerox® Embedded Web Server – Integrated Device Web Pages Provided by the Device	
Device Status	Web server embedded in Network Controller: <ul style="list-style-type: none"> • Tray status/contents • Consumables status • Alerts • Remote Control Panel
Job Submission	Print-ready files: PS, PCL, TIFF, PDF, JPG, TXT, PRN Output feature selection (2-sided, output colour, collate, orientation, staple, hole punch, folding, output destination) Delivery options (Immediate, sample set, delay and secure, Save job or reprint)
Device Administration	Allows simple, remote installation setting of configuration options and management of the device, Fleet Orchestrator
Browsers	Internet Explorer 10.x, 11.x Safari 10.x, 11.x Mozilla Firefox 45.x to 53.x Opera 25.x to 53.x Chrome 48.x to 72.x
Support	Install print / scan drivers and online support available via support.xerox.com
Languages Supported	International English, International French, Italian, German, International Spanish, Dutch, Brazilian Portuguese, Swedish, Norwegian, Danish, Finnish, Russian, Simplified Chinese, Korean, Japanese, Arabic
Remote Services	
Xerox® Automatic Meter Readings (AMR)	Automates the process of collecting and submitting meter reads for the tracking and billing of Xerox® device usage. Eliminates the need for time-consuming end-user involvement and ensures that meter reads are submitted to Xerox on time.
Xerox® Automatic Supplies Replenishment (ASR)	Automatically orders supplies for Xerox® output devices based on actual usage, eliminating the need to manually manage supplies inventory.
Accounting	
Xerox® Standard Accounting (Standard)	
Tracking	Copy, Print, Fax, Scan and Email usage
Accounting	Up to 2,497 User Accounts (User ID) Up to 500 General Accounts (Client) Up to 498 Group Accounts (Department)
Features	<ul style="list-style-type: none"> • Administrator can manage the feature via the Web User Interface or device control panel in tools. • Administrator has the ability to import or export user accounts, Group Accounts, General Accounts and User limits via an industry-standard CSV file.
Accounting Options – Network Accounting (Allows central server to manage all accounting)	
	<ul style="list-style-type: none"> • Enhanced network accounting with up-to-the-minute data on how the system is being used • Comprehensive management and enterprise-scale tracking and reporting of device usage of copy, print, scan and server fax • Numerous solutions are available through Xerox Alliance Partners. For details, visit www.xerox.com • Security enhancements with the addition of HTTPS protocol support • Device requests account authentication from third-party server enabling larger databases of users and accounts • Accept Authentication Login at the control panel and pass to a third-party Networking Account • Interface with a third-party accounting terminal for accounting user interface

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Xerox® EX-c C8100 Print Server Powered by Fiery® (Optional)	
Processor	AMD® GX-424CC processor, 2.4 GHz, Quad-Core, 2M cache
Memory (ESS)	2 GB
System Disk	500 GB HDD
Page Description Language	PostScript v 3020
Features	<ul style="list-style-type: none"> Fiery Command WorkStation for Mac and Windows clients (customer provided) Fiery drivers for Mac and Windows Job Preview Job Presets Image Enhance Spool-RIP-Print simultaneously Automatic two-sided printing N-up Watermarks Calibration PANTONE® Colour Enabled Expert Colour Settings: Profile, Rendering and Simulation Fiery FreeForm Create to create personalised files for free Booklet Maker – booklet wizard to create booklets Standard support for long sheet banners Print from USB flash drive Secure Erase Encryption of critical information Secure Printing User authentication Access controls PostScript security Port blocking IP filtering Digitally signed software updates Fiery API Integrates with common cost accounting software, Xerox Standard Accounting, Xerox App Gallery apps and more
Connectivity	10 Base-T/100 Base-TX/1000 Base-T Ethernet
Optional	<ul style="list-style-type: none"> Fiery Options Bundle (Fiery Spot-On, Auto Trapping, Hot Folders, Virtual Printers), Fiery Hot Folders/Virtual Printers, Fiery Spot-On, Fiery Colour Profiler Suite w/EFI ES-2000 Spectrophotometer, Network Switch to connect both printer and Fiery Server to network

Xerox® AltaLink® C8130/C8135/C8145/C8155/C8170 Colour Multifunction Printer

Supplies	Description	Yield
Toner Cartridge⁶	Black Cyan Magenta Yellow	59,000 pages 28,000 pages 28,000 pages 28,000 pages
Transfer Belt Cleaner	1 Assembly	160,000 pages
Second Bias Transfer Roll	1 Assembly	200,000 pages
Staple Cartridges	For BR Finisher, Integrated Office Finisher, Office Finisher and Convenience Stapler (1 cartridge per carton)	5,000 each cartridge
	For BR Booklet Maker (1 cartridge per carton)	5,000 each cartridge
	For Office Finisher Booklet Maker (8 cartridges per carton)	2,000 each cartridge
Staple Refills	For Integrated Office Finisher, Office Finisher, BR Finisher and Convenience Stapler (3 refills per carton)	5,000 each refill
Fan Filter	1 Assembly (AltaLink C8170)	500,000 pages
Xerox® Smart Kit®		
Drum Cartridge⁸	1 Cartridge per Colour	180,000 pages
Waste Toner Container w/o Suction Filter⁹	1 Cartridge (AltaLink C8130/35/45/55)	69,000 pages
Waste Toner Container with Suction Filter⁹	1 Cartridge (AltaLink C8170)	69,000 pages

¹ Maximum volume capacity expected in any one month. Not expected to be sustained on a regular basis.

² Available post-launch via software update.

³ Not available in all geographical locations.

⁴ Paper capacities are based on 75 gsm stock; capacities will vary with different weight stocks.

⁵ Sold separately in some geographical locations.

⁶ Average standard pages. Declared in accordance with ISO/IEC 19798. Toner yield can vary due to many factors, including but not limited to, image area coverage, image content, media size, media orientation, run mode, application types, monthly print volumes and image quality set-points.

⁷ Under evaluation; certification expected in Q4 2020.

⁸ Average drum yield is based on a run length of 5 pages of A4 LEF pages, with split of 35 % colour / 65 % black-and-white pages.

⁹ Waste Toner Container yield will vary depending on type of image, area coverage % and job run length.

Return spent imaging supplies through the Xerox Green World Alliance collection/reuse/recycling programme.

For more information, visit www.xerox.com/About-Xerox/Recycling.

For more information, visit us at www.xerox.com/Office.